

NCL alltimate is very special premium pure acrylic paint specially formulated to give excellent ultra smooth surface finish. The specially chosen raw materials for making NCL alltimate paint imparts durability, smoothness, excellent surface adhesion, and beauty to the surface.

The surface protecting agents in NCL alltimate offers good protection against common fungi and algae. NCL alltimate also has good tolerance to normal thermal movement and hence offers better protection against surface cracks.

All the precautions of paint surface preparation are to be strictly followed before applying NCL alltimate paint.

NCL alltimate paint is applied with smooth brush and roller over exterior cement plastered and exterior cement primed surfaces in two coats.



Technical Data

Sp. Gravity	1.28
pH	7 to 8.5
Toxicity	non-toxic
Shelf life	12 months in unopened container.
Surface drying	10 to 15 min for touch dry @ normal dry temperature.
Recoating	4 hrs @ normal dry temperature.
Coverage	80 sft / ltrs, however coverage varies with substrate.

Exterior Premium

Features

Premium exterior emulsion paint.

Smooth finish.

Good flexibility.

Easy application with a brush / roller .

Good coverage.

Colour White & Colours as per the shade card.

Packing 20/10/4/1 ltrs. plastic buckets.

Surface preparation

Remove loose sand particles / nibs / fins / oil & grease from the surface.

Fill the surface cavities if any and level the surface.

Dilution Dilute 1 Litre of Alltimate with 1 Liter of water for first coat and 500 ml. of water for second coat.

Application

Apply the material on primed dry surface with a paint brush / roller in two coats.

Allow good surface drying.

DATA provided on this sheet is based on our product knowledge and experience. However applications are beyond our control and the company in no way can stand guarantee. Customers must carry out their tests at site to evaluate product suitability for their applications. For any further assistance the customers are welcome to contact us on