

NCL harmony is an exterior grade emulsion paint specially formulated to give smooth exterior wall paint finishes in various colourful shades.

NCL harmony paint is specially formulated offering water resistance, U.V resistance, and resistance to common fungus and algae. NCL harmony paint has good surface adhesion because of the good acrylic binding medium. NCL harmony also has dry film protective agents giving many years of surface protection.

NCL harmony paint is applied in two coats over cement plastered and primed exterior surface.



Technical Data

Sp. Gravity	1.3
pH	7 to 8
Toxicity	non-toxic
Shelf life	12 months in unopened container.
Surface drying	10 to 15 min @ 30 degrees centigrade temperature.
Recoating time	4 hrs at normal temperatures.
Coverage	60 to 80 Sq.ft/lit. may vary depending upon substrate condition.
VOC	Negligible less than 5%.

Exterior

Features

- Exterior, economical emulsion paint.
- Smooth finish.
- Easy application with a brush / roller .
- Good coverage.

Colour White & Colours as per the shade card.
Packing 20/10/4/1 lits. plastic buckets.

Surface preparation

- Remove loose sand particles / nibs / fins / oil & grease from the surface.
- Fill the surface cavities if any and level the surface.

Dilution Dilute 1 Litre of Harmony with 1 Litre of water for first coat and 500ml. of water for second coat.

Application

- Apply the material on primed dry surface with a paint brush / roller in two coats.
- Allow good surface drying.

DATA provided on this sheet is based on our product knowledge and experience. However applications are beyond our control and the company in no way can stand guarantee. Customers must carry out their tests at site to evaluate product suitability for their applications. For any further assistance the customers are welcome to contact us on